

Delivery Size : 65 mm (2½")				KJM – 262 : MIXED FLOW				Maximum Outer Diameter : 146 mm					
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	3.5	4.5	6.0	7.0	8.5	10.0	11.5	Max. Current (A)
				LPM	0	210	270	360	420	510	600	690	
				LPH	0	12600	16200	21600	25200	30600	36000	41400	
KJM-242/3/3	2.2/3.0	3	DOL	Head in Mtrs.	32	29	26	24	21	18	15	12	7.1
KJM-242/4/4	3.0/4.0	4	DOL		42	38	35	32	28	24	20	16	9.3
KJM-242/5/5	3.7/5.0	5	DOL		53	48	44	40	35	30	25	20	10.9
KJM-242/6/6	4.5/6.0	6	DOL		63	57	53	48	42	36	30	24	13.1
KJM-242/7.5/7	5.5/7.5	7	S/D		74	67	61	56	49	42	35	28	15.8
KJM-242/7.5/8	5.5/7.5	8	S/D		84	76	70	64	56	48	40	32	15.8
KJM-242/10/10	7.5/10.0	10	S/D		105	95	88	80	70	60	50	40	21.2
KJM-242/12.5/12	9.3/12.5	12	S/D		126	114	105	96	84	72	60	48	27.3
KJM-242/15/15	11.0/15.0	15	S/D		158	143	131	120	105	90	75	60	31.6

Delivery Size : 65 mm (2½")				KJM – 262 : MIXED FLOW				Maximum Outer Diameter : 146 mm					
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	4.5	5.75	7.5	9.0	10.5	12.0	13.5	Max. Current (A)
				LPM	0	270	345	450	540	630	720	810	
				LPH	0	16200	20700	27000	32400	37800	43200	48600	
KJM-262/4/3	3.0/4.0	3	DOL	Head in Mtrs.	33	30	27	24	21	18	15	12	9.3
KJM-262/5/4	3.7/5.0	4	DOL		44	40	36	32	28	24	20	16	10.9
KJM-262/6/5	4.5/6.0	5	DOL		55	50	45	40	35	30	25	20	13.1
KJM-262/7.5/6	5.5/7.5	6	S/D		66	60	54	48	42	36	30	24	15.8
KJM-262/10/8	7.5/10.0	8	S/D		88	80	72	64	56	48	40	32	21.2
KJM-262/12.5/10	9.3/12.5	10	S/D		110	100	90	80	70	60	50	40	27.3
KJM-262/15/12	11.0/15.0	12	S/D		132	120	108	96	84	72	60	48	31.6

Delivery Size : 65/80 mm (2½/3")				KJM – 271 : MIXED FLOW				Maximum Outer Diameter : 146 mm					
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	5.0	8.0	9.5	11.0	12.5	14.0	15.5	Max. Current (A)
				LPM	0	300	480	570	660	750	840	930	
				LPH	0	18000	28800	34200	39600	45000	50400	55800	
KJM-271/3/2	2.2/3.0	2	DOL	Head in Mtrs.	22	20	18	16	14	12	10	8	7.1
KJM-271/5/3	3.7/5.0	3	DOL		33	30	27	24	21	18	15	12	10.9
KJM-271/6/4	4.5/6.0	4	DOL		44	40	36	32	28	24	20	16	13.1
KJM-271/7.5/5	5.5/7.5	5	S/D		55	50	45	40	35	30	25	20	15.8
KJM-271/10/7	7.5/10.0	7	S/D		77	70	63	56	49	42	35	28	21.2
KJM-271/12.5/8	9.3/12.5	8	S/D		88	80	72	64	56	48	40	32	27.3
KJM-271/15/10	11.0/15.0	10	S/D		110	100	90	80	70	60	50	40	31.6

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Losses

Delivery Size : 80 mm (3")				KJM – 302 : MIXED FLOW					Maximum Outer Diameter : 146 mm				
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	6.5	10.5	12.5	14.0	18.0	20.0	21.5	Max. Current (A)
				LPM	0	390	630	750	840	1080	1200	1290	
				LPH	0	23400	37800	45000	50400	64800	72000	77400	
KJM-302/4/2	3.0/4.0	2	DOL	Head in Mtrs.	24	20	18	17	15	13	10	8	9.3
KJM-302/6/3	4.5/6.0	3	DOL		36	30	27	25	23	19	15	12	13.1
KJM-302/7.5/4	5.5/7.5	4	S/D		48	40	36	33	30	25	20	16	15.8
KJM-302/7.5/5	5.5/7.5	5	S/D		55	46	42	37	35	29	23	18	15.8
KJM-302/10/5	7.5/10.0	5	S/D		60	50	45	41	38	31	25	20	21.2
KJM-302/10/6	7.5/10.0	6	S/D		66	55	50	45	42	35	28	22	21.2
KJM-302/12.5/6	9.3/12.5	6	S/D		72	60	54	50	45	38	30	24	27.3
KJM-302/15/7	11.0/15.0	7	S/D		84	70	63	58	53	44	35	28	31.6
KJM-302/15/8	11.0/15.0	8	S/D		96	80	72	66	60	50	40	32	31.6

Delivery Size : 80/100 mm (3/4")				KJM – 325 : MIXED FLOW					Maximum Outer Diameter : 146 mm				
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	9.0	12.0	15.0	16.5	19.0	21.0	22.5	Max. Current (A)
				LPM	0	540	720	900	990	1140	1260	1350	
				LPH	0	32400	43200	54000	59400	68400	75600	81000	
KJM-325/5/2	3.7/5.0	2	DOL	Head in Mtrs.	26	22	20	18	16	14	12	10	10.9
KJM-325/7.5/3	5.5/7.5	3	S/D		39	33	30	27	24	21	18	15	15.8
KJM-325/10/4	7.5/10.0	4	S/D		52	44	40	36	32	28	24	20	21.2
KJM-325/12.5/5	9.3/12.5	5	S/D		65	55	50	45	40	35	30	25	27.3
KJM-325/15/6	11.0/15.0	6	S/D		78	66	60	54	48	42	36	30	31.6

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head+Delivery Head+Friction Losses