













Delivery Size : 80/100 mm (3/4")				KJM – 20 : MIXED FLOW				Maximum Outer Diameter : 180 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	5.0	10.0	13.0	15.0	18.0	20.0	22.0	Max. Current (A)	ISI Mark
				LPM	0	300	600	780	900	1080	1200	1320		
				LPH	0	18000	36000	46800	54000	64800	72000	79200		
KJM-20/6/3	4.5/6.0	3	DOL	Head in Mtrs.	33	29	26	23	21	18	15	12	13.1	
KJM-20/7.5/4	5.5/7.5	4	S/D		44	39	35	31	28	24	20	16	15.8	
KJM-20/10/5	7.5/10.0	5	S/D		55	48	43	38	35	30	25	20	21.2	
KJM-20/12.5/6	9.3/12.5	6	S/D		66	58	52	46	42	36	30	24	27.3	
KJM-20/15/7	11.0/15.0	7	S/D		77	68	61	54	49	42	35	28	31.6	
KJM-20/17.5/9	13.0/17.5	9	S/D		99	87	78	69	63	54	45	36	37.1	
KJM-20/20/10	15.0/20.0	10	S/D		110	97	87	77	70	60	50	40	42.6	



Delivery Size : 80/100 mm (3/4")				KJM – 25 : MIXED FLOW				Maximum Outer Diameter : 180 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	6.0	13.0	16.0	19.0	22.0	23.0	26.5	Max. Current (A)	ISI Mark
				LPM	0	360	780	960	1140	1320	1380	1590		
				LPH	0	21600	46800	57600	68400	79200	82800	95400		
KJM-25/5/2	3.7/5.0	2	DOL	Head in Mtrs.	26	24	20	18	16	14	12	10	10.9	
KJM-25/7.5/3	5.5/7.5	3	S/D		39	36	30	27	24	21	18	15	15.8	
KJM-25/10/4 A	7.5/10.0	4	S/D		52	48	40	36	32	28	24	20	21.2	
KJM-25/12.5/5	9.3/12.5	5	S/D		65	60	50	45	40	35	30	25	27.3	
KJM-25/15/6	11.0/15.0	6	S/D		78	72	60	54	48	42	36	30	31.6	
KJM-25/17.5/7	13.0/17.5	7	S/D		91	84	70	63	56	49	42	35	37.1	
KJM-25/20/8	15.0/20.0	8	S/D		104	96	80	72	64	56	48	40	42.6	
KJM-25/25/10	18.5/25.0	10	S/D		130	120	100	90	80	70	60	50	51.9	

Delivery Size : 80/100 mm (3/4")				KJM – 30 : MIXED FLOW				Maximum Outer Diameter : 180 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	9.0	14.0	18.0	21.0	23.5	25.0	27.0	Max. Current (A)	ISI Mark
				LPM	0	540	840	1080	1260	1410	1500	1620		
				LPH	0	32400	50400	64800	75600	84600	90000	97200		
KJM-30/6/2	4.5/6.0	2	DOL	Head in Mtrs.	32	26	23	20	18	16	14	12	13.1	
KJM-30/10/3	7.5/10.0	3	S/D		48	39	35	30	27	24	21	18	21.2	
KJM-30/12.5/4	9.3/12.5	4	S/D		64	52	46	40	36	32	28	24	27.3	
KJM-30/15/5	11.0/15.0	5	S/D		80	65	58	50	45	40	35	30	31.6	
KJM-30/17.5/6	13.0/17.5	6	S/D		96	78	69	60	54	48	42	36	37.1	
KJM-30/20/7	15.0/20.0	7	S/D		112	91	81	70	63	56	49	42	42.6	
KJM-30/25/8	18.5/25.0	8	S/D		128	104	92	80	72	64	56	48	51.9	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head+ Delivery Head+ Friction Losses

Delivery Size : 80/100 mm (3"/4")				KJM – 40 : MIXED FLOW				Maximum Outer Diameter : 180 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	9.5	13.0	16.0	19.5	22.0	24.0	25.5	Max. Current (A)	ISI Mark
				LPM	0	570	780	960	1170	1320	1440	1530		
				LPH	0	34200	46800	57600	70200	79200	86400	91800		
KJM-40/7.5/2	5.5/7.5	2	DOL	Head in Mtrs.	35	30	28	25	22	20	18	16	15.8	
KJM-40/12.5/3	9.3/12.5	3	S/D		53	45	42	38	33	30	27	24	27.3	
KJM-40/15/4	11.0/15.0	4	S/D		70	60	56	50	44	40	36	32	31.6	
KJM-40/20/5	15.0/20.0	5	S/D		88	75	70	63	55	50	45	40	42.6	
KJM-40/25/6	18.5/25.0	6	S/D		105	90	84	75	66	60	54	48	51.9	

Delivery Size : 80/100 mm (3"/4")				KJM – 50 : MIXED FLOW				Maximum Outer Diameter : 180 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	10.0	13.5	16.0	20.0	21.5	23.0	24.5	Max. Current (A)	ISI Mark
				LPM	0	600	810	960	1200	1290	1380	1470		
				LPH	0	36000	48600	57600	72000	77400	82800	88200		
KJM-50/10/2	7.5/10.0	2	S/D	Head in Mtrs.	38	32	29	27	24	22	20	18	21.2	
KJM-50/15/3	11.0/15.0	3	S/D		57	48	44	41	36	33	30	27	31.6	
KJM-50/20/4	15.0/20.0	4	S/D		76	64	58	54	48	44	40	36	42.6	
KJM-50/25/5	18.5/25.0	5	S/D		95	80	73	68	60	55	50	45	51.9	

Delivery Size : 80/100 mm (3"/4")				KJM – 60 : MIXED FLOW				Maximum Outer Diameter : 180 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	12.0	17.0	20.0	23.5	25.0	26.5	28.5	Max. Current (A)	ISI Mark
				LPM	0	720	1020	1200	1410	1500	1590	1710		
				LPH	0	43200	61200	72000	84600	90000	95400	102600		
KJM-60/12.5/2	9.3/12.5	2	S/D	Head in Mtrs.	39	33	31	28	26	24	22	20	27.3	
KJM-60/17.5/3	13.0/17.5	3	S/D		59	50	47	42	39	36	33	30	37.1	
KJM-60/25/4	18.5/25.0	4	S/D		78	66	62	56	52	48	44	40	51.9	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head+ Delivery Head + Friction Los ses