

Delivery Size : 50 mm (2")				KR – 40 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	1.4	2.0	2.3	2.8	3.3	3.8	4.1	Max. Current (A)	ISI Mark
				LPM	0	84	120	138	168	1100	228	246		
				LPH	0	5040	7200	8280	10080	11880	13680	14760		
KR-40/3/8	2.2/3.0	8	DOL	Head in Mtrs.	84	78	72	66	60	56	48	40	7.1	
KR-40/4/10	3.0/4.0	10	DOL		105	100	90	83	75	70	60	50	9.3	
KR-40/5/12	3.7/5.0	12	DOL		126	117	108	99	90	84	72	60	10.9	
KR-40/6/15	4.5/6.0	15	DOL		158	146	135	124	113	105	90	75	13.1	
KR-40/7.5/18	5.5/7.5	18	S/D		189	176	162	149	135	126	108	90	15.8	
KR-40/7.5/20	5.5/7.5	20	S/D		210	195	180	165	150	140	120	100	15.8	
KR-40/10/25	7.5/10.0	25	S/D		263	244	225	206	188	175	150	125	21.2	
KR-40/12.5/30	9.3/12.5	30	S/D		315	293	270	248	225	210	180	150	27.3	
KR-40/15/38	11.0/15.0	38	S/D		399	371	342	314	285	266	228	190	31.6	









Delivery Size : 50 mm (2")				KR – 50 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	2.0	2.7	3.0	3.5	4.0	4.4	4.7	Max. Current (A)	ISI Mark
				LPM	0	120	162	180	210	240	264	282		
				LPH	0	7200	9720	10800	12600	14400	15840	16920		
KR-50/3/6	2.2/3.0	6	DOL	Head in Mtrs.	69	57	54	50	45	42	36	30	7.1	
KR-50/4/8	3.0/4.0	8	DOL		92	76	72	66	60	56	48	40	9.3	
KR-50/5/10	3.7/5.0	10	DOL		115	95	90	83	75	70	60	50	10.9	
KR-50/6/12	4.5/6.0	12	DOL		138	114	108	99	90	84	72	60	13.1	
KR-50/7.5/14	5.5/7.5	14	S/D		161	133	126	116	105	100	84	70	15.8	
KR-50/7.5/15	5.5/7.5	15	S/D		173	143	135	124	113	105	90	75	15.8	
KR-50/10/20	7.5/10.0	20	S/D		230	190	180	165	150	140	120	100	21.2	
KR-50/12.5/25	9.3/12.5	25	S/D		288	238	225	206	188	175	150	125	27.3	
KR-50/15/30	11.0/15.0	30	S/D		345	285	270	248	225	210	180	150	31.6	

Delivery Size : 50 mm (2")				KR – 60 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	2.8	3.3	3.8	4.2	4.7	5.2	5.5	Max. Current (A)	ISI Mark
				LPM	0	168	1100	228	252	282	312	330		
				LPH	0	10080	11880	13680	15120	16920	18720	110000		
KR-60/3/5	2.2/3.0	5	DOL	Head in Mtrs.	60	50	47	44	40	35	30	25	7.1	
KR-60/4/7	3.0/4.0	7	DOL		84	70	66	61	56	49	42	35	9.3	
KR-60/5/8	3.7/5.0	8	DOL		96	80	75	70	64	56	48	40	10.9	
KR-60/6/10	4.5/6.0	10	DOL		120	100	94	88	80	70	60	50	13.1	
KR-60/7.5/12	5.5/7.5	12	S/D		144	120	113	105	96	84	72	60	15.8	
KR-60/10/16	7.5/10.0	16	S/D		192	160	150	140	128	112	96	80	21.2	
KR-60/12.5/20	9.3/12.5	20	S/D		240	200	188	175	160	140	120	100	27.3	
KR-60/15/24	11.0/15.0	24	S/D		288	240	226	210	192	168	144	120	31.6	
KR-60/17.5/28	13.0/17.5	28	S/D		336	280	263	245	224	196	168	140	37.1	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head+ Delivery Head + Friction Losses










Delivery Size : 50 mm (2")				KR – 70 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	3.2	3.7	4.1	4.6	5.1	5.5	5.8	Max. Current (A)	ISI Mark
				LPM	0	192	222	246	276	306	330	348		
				LPH	0	11520	13320	14760	16560	18360	110000	20880		
KR-70/3/4	2.2/3.0	4	DOL	Head in Mtrs.	48	40	37	35	32	28	24	20	7.1	
KR-70/4/6	3.0/4.0	6	DOL		72	60	56	53	48	42	36	30	9.3	
KR-70/5/7	3.7/5.0	7	DOL		84	70	65	62	56	49	42	35	10.9	
KR-70/6/9	4.5/6.0	9	DOL		108	90	84	80	72	63	54	45	13.1	
KR-70/7.5/11	5.5/7.5	11	S/D		132	110	103	97	88	77	66	55	15.8	
KR-70/10/14	7.5/10.0	14	S/D		168	140	131	124	112	100	84	70	21.2	
KR-70/12.5/16	9.3/12.5	16	S/D		192	160	149	141	128	112	96	80	27.3	
KR-70/15/20	11.0/15.0	20	S/D		240	200	187	177	160	140	120	100	31.6	
KR-70/17.5/24	13.0/17.5	24	S/D		288	240	224	212	192	168	144	120	37.1	
KR-70/20/28	15.0/20.0	28	S/D		336	280	261	247	224	196	168	140	42.6	

Delivery Size : 50 mm (2")				KR – 80 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	3.6	4.1	4.5	5.0	5.4	5.8	6.2	Max. Current (A)	ISI Mark
				LPM	0	216	246	270	300	324	348	372		
				LPH	0	12960	14760	16200	18000	19440	20880	22320		
KR-80/3/4	2.2/3.0	4	DOL	Head in Mtrs.	48	40	37	35	32	28	24	20	7.1	
KR-80/4/5	3.0/4.0	5	DOL		60	50	47	44	40	35	30	25	9.3	
KR-80/5/6	3.7/5.0	6	DOL		72	60	56	53	48	42	36	30	10.9	
KR-80/6/8	4.5/6.0	8	DOL		96	80	75	71	64	56	48	40	13.1	
KR-80/7.5/10	5.5/7.5	10	S/D		120	100	93	88	80	70	60	50	15.8	
KR-80/10/12	7.5/10.0	12	S/D		144	120	112	106	96	84	72	60	21.2	
KR-80/12.5/14	9.3/12.5	14	S/D		168	140	131	124	112	100	84	70	27.3	
KR-80/15/18	11.0/15.0	18	S/D		216	180	168	159	144	126	108	90	31.6	
KR-80/17.5/20	13.0/17.5	20	S/D		240	200	187	177	160	140	120	100	37.1	
KR-80/20/24	15.0/20.0	24	S/D		288	240	224	212	192	168	144	120	42.6	
KR-80/25/30	18.5/25.0	30	S/D		360	300	280	265	240	210	180	150	51.7	

Delivery Size : 50 mm (2")				KR – 90 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	4.0	4.4	4.9	5.4	5.8	6.2	6.6	Max. Current (A)	ISI Mark
				LPM	0	240	264	294	324	348	372	396		
				LPH	0	14400	15840	17640	19440	20880	22320	23760		
KR-90/3/3	2.2/3.0	3	DOL	Head in Mtrs.	36	30	28	27	24	21	18	15	7.1	
KR-90/4/5	3.0/4.0	5	DOL		60	50	47	44	40	35	30	25	9.3	
KR-90/5/6	3.7/5.0	6	DOL		72	60	56	53	48	42	36	30	10.9	
KR-90/6/7	4.5/6.0	7	DOL		84	70	65	62	56	49	42	35	13.1	
KR-90/7.5/9	5.5/7.5	9	S/D		108	90	84	80	72	63	54	45	15.8	
KR-90/10/11	7.5/10.0	11	S/D		132	110	103	97	88	77	66	55	21.2	
KR-90/12.5/13	9.3/12.5	13	S/D		156	130	121	115	104	91	78	65	27.3	
KR-90/15/17	11.0/15.0	17	S/D		204	170	159	150	136	119	102	85	31.6	
KR-90/17.5/19	13.0/17.5	19	S/D		228	190	177	168	152	133	114	95	37.1	
KR-90/20/22	15.0/20.0	22	S/D		264	220	205	194	176	154	132	110	42.6	
KR-90/25/28	18.5/25.0	28	S/D		336	280	261	247	224	196	168	140	51.7	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Losses

Delivery Size : 50 mm (2")				KR – 100 : RADIAL FLOW				Maximum Outer Diameter : 146 mm				Max. Current (A)	ISI Mark	
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	4.3	4.8	5.3	5.8	6.2	6.6			7.0
				LPM	0	258	288	318	348	372	396			420
				LPH	0	15480	17280	19080	20880	22320	23760			25200
KR-100/3/3	2.2/3.0	3	DOL	Head in Mtrs.	36	30	28	27	24	21	18	15	7.1	
KR-100/4/4	3.0/4.0	4	DOL		48	40	37	35	32	28	24	20	9.3	
KR-100/5/5	3.7/5.0	5	DOL		60	50	47	44	40	35	30	25	10.9	
KR-100/6/6	4.5/6.0	6	DOL		72	60	56	53	48	42	36	30	13.1	
KR-100/7.5/7	5.5/7.5	7	S/D		84	70	65	62	56	49	42	35	15.8	
KR-100/7.5/8	5.5/7.5	8	S/D		96	80	75	71	64	56	48	40	15.8	
KR-100/10/10	7.5/10.0	10	S/D		120	100	93	88	80	70	60	50	21.2	
KR-100/12.5/12	9.3/12.5	12	S/D		144	120	112	106	96	84	72	60	27.3	
KR-100/15/15	11.0/15.0	15	S/D		180	150	140	133	120	105	90	75	31.6	
KR-100/17.5/18	13.0/17.5	18	S/D		216	180	168	159	144	126	108	90	37.1	
KR-100/20/20	15.0/20.0	20	S/D		240	200	187	177	160	140	120	100	42.6	
KR-100/25/25	18.5/25.0	25	S/D		300	250	233	221	200	175	150	125	51.7	

Delivery Size : 50/65 mm (2/2½")				KR – 120 : RADIAL FLOW				Maximum Outer Diameter : 146 mm				Max. Current (A)	ISI Mark	
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	5.0	5.7	6.3	6.8	7.2	7.6			8.0
				LPM	0	300	342	378	408	432	456			480
				LPH	0	18000	20520	22680	24480	25920	27360			28800
KR-120/4/3	3.0/4.0	3	DOL	Head in Mtrs.	35	33	31	28	25	21	18	15	9.3	
KR-120/5/4	3.7/5.0	4	DOL		47	44	41	37	33	28	23	20	10.9	
KR-120/6/5	4.5/6.0	5	DOL		58	55	52	47	41	35	29	25	13.1	
KR-120/7.5/6	5.5/7.5	6	S/D		70	66	62	56	49	42	35	30	15.8	
KR-120/10/8	7.5/10.0	8	S/D		93	88	83	75	65	56	47	40	21.2	
KR-120/12.5/10	9.3/12.5	10	S/D		117	110	103	93	82	70	58	50	27.3	
KR-120/15/12	11.0/15.0	12	S/D		140	132	124	112	100	84	70	60	31.6	
KR-120/17.5/14	13.0/17.5	14	S/D		163	154	145	131	114	96	82	70	37.1	
KR-120/20/16	15.0/20.0	16	S/D		187	176	165	149	131	112	93	80	42.6	
KR-120/25/20	18.5/25.0	20	S/D		233	220	207	187	163	140	117	100	51.7	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head+ Delivery Head + Friction Losses

Delivery Size : 65 mm (2½")				KRH – 60 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	1.7	2.1	2.5	2.7	3.2	3.5	3.9	Max. Current (A)	ISI Mark
				LPM	0	102	126	150	162	192	210	234		
				LPH	0	6120	7560	9000	9720	11520	12600	14040		
KRH-60/3/5	2.2/3.0	5	DOL	Head in Mtrs.	78	74	70	65	60	53	45	40	7.1	
KRH-60/4/7	3.0/4.0	7	DOL		109	103	100	91	84	74	63	56	9.3	
KRH-60/5/8	3.7/5.0	8	DOL		124	118	112	104	96	84	72	64	10.9	
KRH-60/6/10	4.5/6.0	10	DOL		155	147	140	130	120	105	90	80	13.1	
KRH-60/7.5/12	5.5/7.5	12	S/D		186	176	168	156	144	126	108	96	15.8	
KRH-60/10/16	7.5/10.0	16	S/D		248	235	224	208	192	168	144	128	21.2	
KRH-60/12.5/20	9.3/12.5	20	S/D		310	294	280	260	240	210	180	160	27.3	
KRH-60/15/24	11.0/15.0	24	S/D		372	353	336	312	288	252	216	192	31.6	
KRH-60/17.5/27	13.0/17.5	27	S/D		419	397	378	351	324	284	243	216	37.1	
KRH-60/20/30	15.0/20.0	30	S/D		465	441	420	390	360	315	270	240	42.6	
Delivery Size : 65 mm (2½")				KRH – 80 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	1.9	2.5	3.1	3.5	3.9	4.5	4.9	Max. Current (A)	ISI Mark
				LPM	0	114	150	186	210	234	270	294		
				LPH	0	6840	9000	11160	12600	14040	16200	17640		
KRH-80/3/4	2.2/3.0	4	DOL	Head in Mtrs.	63	59	56	52	48	42	36	32	7.1	
KRH-80/4/5	3.0/4.0	5	DOL		79	74	70	65	60	53	45	40	9.3	
KRH-80/5/6	3.7/5.0	6	DOL		95	89	84	78	72	64	54	48	10.9	
KRH-80/6/8	4.5/6.0	8	DOL		126	118	112	104	96	85	72	64	13.1	
KRH-80/7.5/10	5.5/7.5	10	S/D		158	148	140	130	120	106	90	80	15.8	
KRH-80/10/12	7.5/10.0	12	S/D		190	178	168	156	144	127	108	96	21.2	
KRH-80/12.5/15	9.3/12.5	15	S/D		237	222	210	195	180	159	135	120	27.3	
KRH-80/15/18	11.0/15.0	18	S/D		284	266	252	234	216	191	162	144	31.6	
KRH-80/17.5/21	13.0/17.5	21	S/D		332	311	294	273	252	223	189	168	37.1	
KRH-80/20/24	15.0/20.0	24	S/D		379	355	336	312	288	254	216	192	42.6	
KRH-80/25/30	18.5/25.0	30	S/D	474	444	420	390	360	318	270	240	51.7		
Delivery Size : 65 mm (2½")				KRH – 100 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	2.3	3.0	3.7	4.2	4.6	5.3	5.7	Max. Current (A)	ISI Mark
				LPM	0	138	180	222	252	276	318	342		
				LPH	0	8280	10800	13320	15120	16560	19080	20520		
KRH-100/3/3	2.2/3.0	3	DOL	Head in Mtrs.	47	44	42	39	36	32	27	24	7.1	
KRH-100/4/4	3.0/4.0	4	DOL		63	59	56	52	48	42	36	32	9.3	
KRH-100/5/5	3.7/5.0	5	DOL		79	74	70	65	60	53	45	40	10.9	
KRH-100/6/6	4.5/6.0	6	DOL		95	89	84	78	72	64	54	48	13.1	
KRH-100/7.5/7	5.5/7.5	7	S/D		111	104	100	91	84	74	63	56	15.8	
KRH-100/7.5/8	5.5/7.5	8	S/D		126	118	112	104	96	85	72	64	15.8	
KRH-100/10/10	7.5/10.0	10	S/D		158	148	140	130	120	106	90	80	21.2	
KRH-100/12.5/12	9.3/12.5	12	S/D		190	178	168	156	144	127	108	96	27.3	
KRH-100/15/15	11.0/15.0	15	S/D		237	222	210	195	180	159	135	120	31.6	
KRH-100/17.5/18	13.0/17.5	18	S/D		284	266	252	234	216	191	162	144	37.1	
KRH-100/20/20	15.0/20.0	20	S/D	316	296	280	260	240	212	180	160	42.6		
KRH-100/25/25	18.5/25.0	25	S/D	395	370	350	325	300	265	225	200	51.7		









Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.










Total Head=Suction Head + Delivery Head + Friction Losses




Delivery Size : 65 mm (2½")				KRH – 125 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	3.0	3.5	4.5	5.5	6.2	7.0	7.6	Max. Current (A)	ISI Mark
				LPM	0	180	210	270	330	372	420	456		
				LPH	0	10800	12600	16200	110000	22320	25200	27360		
KRH-125/4/3	3.0/4.0	3	DOL	Head in Mtrs.	47	44	42	39	36	32	27	24	9.3	
KRH-125/5/4	3.7/5.0	4	DOL		63	59	56	52	48	42	36	32	10.9	
KRH-125/6/5	4.5/6.0	5	DOL		79	74	70	65	60	53	45	40	13.1	
KRH-125/7.5/6	5.5/7.5	6	S/D		95	89	84	78	72	64	54	48	15.8	
KRH-125/10/8	7.5/10.0	8	S/D		126	118	112	104	96	85	72	64	21.2	
KRH-125/12.5/10	9.3/12.5	10	S/D		158	148	140	130	120	106	90	80	27.3	
KRH-125/15/12	11.0/15.0	12	S/D		190	178	168	156	144	127	108	96	31.6	
KRH-125/17.5/14	13.0/17.5	14	S/D		221	207	196	182	168	148	126	112	37.1	
KRH-125/20/16	15.0/20.0	16	S/D		253	237	224	208	192	170	144	128	42.6	
Delivery Size : 65 mm (2½")				KRH – 150 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	4.2	4.8	5.5	6.4	7.2	7.7	8.2	Max. Current (A)	ISI Mark
				LPM	0	252	288	330	384	432	462	492		
				LPH	0	15120	17280	110000	23040	25920	27720	29520		
KRH-150/3/2	2.2/3.0	2	DOL	Head in Mtrs.	32	30	28	26	24	22	18	16	7.1	
KRH-150/5/3	3.7/5.0	3	DOL		48	44	42	39	36	32	27	24	10.9	
KRH-150/6/4	4.5/6.0	4	DOL		64	59	56	52	48	43	36	32	13.1	
KRH-150/7.5/5	5.5/7.5	5	S/D		80	74	70	65	60	54	45	40	15.8	
KRH-150/10/7	7.5/10.0	7	S/D		112	104	100	91	84	75	63	56	21.2	
KRH-150/12.5/8	9.3/12.5	8	S/D		128	118	112	104	96	86	72	64	27.3	
KRH-150/15/10	11.0/15.0	10	S/D		160	148	140	130	120	108	90	80	31.6	
KRH-150/17.5/12	13.0/17.5	12	S/D		192	178	168	156	144	130	108	96	37.1	
KRH-150/20/14	15.0/20.0	14	S/D		224	207	196	182	168	151	126	112	42.6	
KRH-150/25/16	18.5/25.0	16	S/D	256	237	224	208	192	173	144	128	51.7		
Delivery Size : 65 mm (2½")				KRH – 200 : RADIAL FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	4.9	5.6	6.4	7.5	8.4	9.0	9.6	Max. Current (A)	ISI Mark
				LPM	0	294	336	384	450	504	540	576		
				LPH	0	17640	20160	23040	27000	30240	32400	34560		
KRH-200/4/2	3.0/4.0	2	DOL	Head in Mtrs.	32	30	28	26	24	21	18	16	9.3	
KRH-200/6/3	4.5/6.0	3	DOL		48	45	42	39	36	32	27	24	13.1	
KRH-200/7.5/4	5.5/7.5	4	S/D		64	60	56	52	48	42	36	32	15.8	
KRH-200/10/5	7.5/10.0	5	S/D		80	75	70	65	60	53	45	40	21.2	
KRH-200/12.5/6	9.3/12.5	6	S/D		96	90	84	84	72	63	54	48	27.3	
KRH-200/15/8	11.0/15.0	8	S/D		128	120	112	104	96	84	72	64	31.6	
KRH-200/17.5/9	13.0/17.5	9	S/D		144	135	126	117	108	95	81	72	37.1	
KRH-200/20/10	15.0/20.0	10	S/D		160	150	140	130	120	105	90	80	42.6	
KRH-200/25/12	18.5/25.0	12	S/D		192	180	168	156	144	126	108	96	51.7	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Los ses










Delivery Size : 65 mm (2½")				K – 242 : MIXED FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	3.5	4.5	6.0	7.0	8.5	10.0	11.5	Max. Current (A)	ISI Mark
				LPM	0	210	270	360	420	510	600	690		
				LPH	0	12600	16200	21600	25200	30600	36000	41400		
K-242/3/3	2.2/3.0	3	DOL	Head in Mtrs.	32	29	26	24	21	18	15	12	7.1	
K-242/4/4	3.0/4.0	4	DOL		42	38	35	32	28	24	20	16	9.3	
K-242/5/5	3.7/5.0	5	DOL		53	48	44	40	35	30	25	20	10.9	
K-242/6/6	4.5/6.0	6	DOL		63	57	53	48	42	36	30	24	13.1	
K-242/7.5/7	5.5/7.5	7	S/D		74	67	61	56	49	42	35	28	15.8	
K-242/7.5/8	5.5/7.5	8	S/D		84	76	70	64	56	48	40	32	15.8	
K-242/10/10	7.5/10.0	10	S/D		105	95	88	80	70	60	50	40	21.2	
K-242/12.5/12	9.3/12.5	12	S/D		126	114	105	96	84	72	60	48	27.3	
K-242/15/15	11.0/15.0	15	S/D		158	143	131	120	105	90	75	60	31.6	
K-242/17.5/17	13.0/17.5	17	S/D		179	162	149	136	119	102	85	68	37.1	
K-242/20/19	15.0/20.0	19	S/D		200	181	166	152	133	114	95	76	42.6	

Delivery Size : 65 mm (2½")				K – 262 : MIXED FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	4.5	5.7	7.5	9.0	10.5	12.0	13.5	Max. Current (A)	ISI Mark
				LPM	0	270	342	450	540	630	720	810		
				LPH	0	16200	20520	27000	32400	37800	43200	48600		
K-262/4/3	3.0/4.0	3	DOL	Head in Mtrs.	33	30	27	24	21	18	15	12	9.3	
K-262/5/4	3.7/5.0	4	DOL		44	40	36	32	28	24	20	16	10.9	
K-262/6/5	4.5/6.0	5	DOL		55	50	45	40	35	30	25	20	13.1	
K-262/7.5/6	5.5/7.5	6	S/D		66	60	54	48	42	36	30	24	15.8	
K-262/10/8	7.5/10.0	8	S/D		88	80	72	64	56	48	40	32	21.2	
K-262/12.5/10	9.3/12.5	10	S/D		110	100	90	80	70	60	50	40	27.3	
K-262/15/12	11.0/15.0	12	S/D		132	120	108	96	84	72	60	48	31.6	
K-262/17.5/14	13.0/17.5	14	S/D		154	140	126	112	100	84	70	56	37.1	
K-262/20/16	15.0/20.0	16	S/D		176	160	144	128	112	96	80	64	42.6	
K-262/25/19	18.5/25.0	19	S/D		209	190	171	152	133	114	95	76	51.9	

Delivery Size : 65/80 mm (2½/3")				K – 271 : MIXED FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	6.0	8.0	9.5	11.0	12.5	14.0	15.5	Max. Current (A)	ISI Mark
				LPM	0	360	480	570	660	750	840	930		
				LPH	0	21600	28800	34200	39600	45000	50400	55800		
K-271/3/2	2.2/3.0	2	DOL	Head in Mtrs.	22	20	18	16	14	12	10	8	7.1	
K-271/5/3	3.7/5.0	3	DOL		33	30	27	24	21	18	15	12	10.9	
K-271/6/4	4.5/6.0	4	DOL		44	40	36	32	28	24	20	16	13.1	
K-271/7.5/5	5.5/7.5	5	S/D		55	50	45	40	35	30	25	20	15.8	
K-271/10/7	7.5/10.0	7	S/D		77	70	63	56	49	42	35	28	21.2	
K-271/12.5/8	9.3/12.5	8	S/D		88	80	72	64	56	48	40	32	27.3	
K-271/15/10	11.0/15.0	10	S/D		110	100	90	80	70	60	50	40	31.6	
K-271/17.5/11	13.0/17.5	11	S/D		121	110	99	88	77	66	55	44	37.1	
K-271/17.5/12	13.0/17.5	12	S/D		132	120	108	96	84	72	60	48	37.1	
K-271/20/13	15.0/20.0	13	S/D		143	130	117	104	91	78	65	52	42.6	
K-271/20/14	15.0/20.0	14	S/D		154	140	126	112	100	84	70	56	42.6	
K-271/25/16	18.5/25.0	16	S/D		176	160	144	128	112	96	80	64	51.9	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Los ses

Delivery Size : 80 mm (3")				K – 302 : MIXED FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	7.0	11.0	12.5	14.0	18.0	20.0	21.5	Max. Current (A)	ISI Mark
				LPM	0	420	660	750	840	1080	1200	1290		
				LPH	0	25200	39600	45000	50400	64800	72000	77400		
K-302/4/2	3.0/4.0	2	DOL	Head in Mtrs.	24	20	18	17	15	13	10	8	9.3	
K-302/6/3	4.5/6.0	3	DOL		36	30	27	25	22	19	15	12	13.1	
K-302/7.5/4	5.5/7.5	4	S/D		48	40	36	33	30	25	20	16	15.8	
K-302/7.5/5	5.5/7.5	5	S/D		55	46	42	37	35	29	23	18	15.8	
K-302/10/5	7.5/10.0	5	S/D		60	50	45	41	38	31	25	20	21.2	
K-302/10/6	7.5/10.0	6	S/D		66	55	50	45	42	35	28	22	21.2	
K-302/12.5/6	9.3/12.5	6	S/D		72	60	54	50	45	38	30	24	27.3	
K-302/15/7	11.0/15.0	7	S/D		84	70	63	58	53	44	35	28	31.6	
K-302/15/8	11.0/15.0	8	S/D		96	80	72	66	60	50	40	32	31.6	
K-302/17.5/9	13.0/17.5	9	S/D		108	90	81	74	68	56	45	36	37.1	
K-302/20/10	15.0/20.0	10	S/D		120	100	90	83	75	63	50	40	42.6	
K-302/25/12	18.5/25.0	12	S/D		144	120	108	99	90	75	60	48	51.9	

Delivery Size : 80/100 mm (3/4")				K – 325 : MIXED FLOW				Maximum Outer Diameter : 146 mm						
Pump Model	Motor Rating kW/HP	Stages	Conn. (Starter)	LPS	0	9.0	12.0	15.0	16.5	19.0	21.0	22.5	Max. Current (A)	ISI Mark
				LPM	0	540	720	900	990	1140	1260	1350		
				LPH	0	32400	43200	54000	59400	68400	75600	81000		
K-325/5/2	3.7/5.0	2	DOL	Head in Mtrs.	26	22	20	18	16	14	12	10	10.9	
K-325/7.5/3	5.5/7.5	3	S/D		39	33	30	27	24	21	18	15	15.8	
K-325/10/4	7.5/10.0	4	S/D		52	44	40	36	32	28	24	20	21.2	
K-325/12.5/5	9.3/12.5	5	S/D		65	55	50	45	40	35	30	25	27.3	
K-325/15/6	11.0/15.0	6	S/D		78	66	60	54	48	42	36	30	31.6	
K-325/17.5/7	13.0/17.5	7	S/D		91	77	70	63	56	49	42	35	37.1	
K-325/20/8	15.0/20.0	8	S/D		104	88	80	72	64	56	48	40	42.6	
K-325/20/9	15.0/20.0	9	S/D		117	99	90	81	72	63	54	45	42.6	
K-325/25/10	18.5/25.0	10	S/D		130	110	100	90	80	70	60	50	51.9	

Statutory Disclaimer:- In view of continual development, the performance figures / information / description / illustrations are subject to change without any prior notice. The performance data given is based on results achieved during tests conducted under ideal test conditions in a laboratory. Actual site conditions may result in variation in these performance values. Depending upon customer feedback and continual improvement, new models are introduced on regular basis, kindly consult your local dealer/re-seller for appropriate pump selection.

Total Head=Suction Head + Delivery Head + Friction Losses